







Abmessung	kg / mtr
Breitflanschträger IPB-HEB-DIN1025 normale Reihe 	
100	20,90
120	27,40
140	34,50
160	43,70
180	52,50
200	63,00
220	73,00
240	85,00
260	95,00
280	106,00
300	120,00
320	130,00
340	137,00
360	146,00
400	159,00
450	175,00
500	192,00
550	204,00
600	217,00

Abmessung	kg / mtr
Mittelbreite I - Träger IPE-DIN1025-5 normale Reihe 	
80	6,20
100	8,30
120	10,70
140	13,20
160	16,20
180	19,30
200	23,00
220	26,90
240	31,50
270	37,00
300	43,30
330	50,40
360	58,60
400	68,00
450	80,00
500	93,00
550	109,00
600	125,00

Abmessung	kg / mtr
Breitflanschträger IPBI-HEA-DIN1025 leichte Reihe 	
100	17,10
120	20,40
140	25,30
160	31,20
180	36,40
200	43,00
220	52,00
240	62,00
260	70,00
280	78,00
300	90,00
320	100,00
340	108,00
360	115,00
400	128,00
450	143,00
500	159,00
550	170,00
600	182,00

Abmessung	kg / mtr
Schmale I - Träger INP nach DIN1025 leichte Reihe 	
80	6,10
100	8,50
120	11,50
140	14,70
160	18,50
180	22,50
200	27,00
220	32,00
240	37,00
260	43,00
280	49,00
300	56,00
320	63,00
340	70,00
360	78,00
400	95,00
450	118,00
500	145,00

Abmessung	kg / mtr
Breitflanschträger IPBv-HEM-DIN1025 verstärkte Reihe 	
100	42,80
120	53,40
140	64,80
160	78,10
180	91,10
200	106,00
220	120,00
240	161,00
260	176,00
280	194,00
300	244,00
320	251,00
340	254,00
360	256,00
400	262,00
450	270,00
500	277,00
550	285,00
600	292,00

Abmessung	kg / mtr
U - Stahl UNP nach DIN1026 innen rundkantig 	
80	8,90
100	10,90
120	13,70
140	16,40
160	19,30
180	22,50
200	26,00
220	30,00
240	34,00
260	38,00
280	43,00
300	48,00
320	61,00
350	62,00
380	65,00
400	74,00